

Nova Down Lights

ITEM SKU#: 662187496405





CE

COB LED





Product C	Code :	IK-RNOVADL	-12W-30K-WH-90C-36D
-----------	--------	-------------------	---------------------

Voltage	100 - 277 V AC, 50-60 Hz	
Lumen Output	1080lm	
Power	12W	
Efficacy	90lm/w	
ССТ	3000K	
CRI	>90	
Beam Angle	36°	
Light Distribution	Flood	
LED Light Source	Osram SOLERIQ S 19	
Start Time	Instant	
Driver	Stand Alone (included)	
Operating Position	Swiveling Type, 360D	
Dimming	On-Off / Triac / 0-10 V	
Construction	Round	
Mounting Type	Recessed	
Heads	Single Head	
Body Material	Aluminium Die cast	
Finish	White	
Height	3-1/8"	
Diameter	3-1/2"	
Cut Out	3-1/8"	
Optics	Darklight Technology Black, Silver	
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance	

Beam Spread (Options) Spot Medium <mark>24°</mark> Ø Flood ft ft ft Ø 1.41 3.0 0.72 3.0 3.0

9.0

2.15 15.0

3.58

9.0

15.0

4.22 9.0

7.04

15.0

<mark>36°</mark> Ø

2.03

6.09

10.15

Nova, a round shaped LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. The specular darklight reflector in this store light allows outstanding visual comfort to the visitors so that they are able to explore the merchandise at ease.

🖲 Ikio



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.