


Ocul Down Lights

ITEM SKU#: 662187497723



Product Code : IK-ROCULDL-50W-35K-WH-90C-60D

| | |
|--------------------|---|
| Voltage | 100 - 277 V AC, 50-60 Hz |
| Lumen Output | 6650lm |
| Power | 50W |
| Efficacy | 140lm/w |
| CCT | 3500K |
| CRI | >90 |
| Beam Angle | 60° |
| Light Distribution | Wide flood |
| LED Type | COB |
| LED Light Source | Osram SOLERIQ S 19 |
| Start Time | Instant |
| Driver | Stand Alone (included) |
| Operating Position | Non - Swiveling Type |
| Dimming | On-Off / Triac / 0-10 V |
| Construction | Round |
| Mounting Type | Recessed |
| Heads | Single Head |
| Body Material | Aluminium Die cast |
| Finish | White |
| Height | 4" |
| Diameter | 7-1/2" |
| Cut Out | 6-7/8" |
| Optics | Darklight Technology Black, Silver |
| Application Area | Classroom, Meeting Room, Office, Club, Home |

| Beam Spread (Options) | | | | | | | | | | | |
|-----------------------|------|--|------------|------|--|-----------|-------|--|----------------|-------|--|
| Spot 15° | | | Medium 24° | | | Flood 36° | | | Wide Flood 60° | | |
| ft | Ø | | ft | Ø | | ft | Ø | | ft | Ø | |
| 3.0 | 0.72 | | 3.0 | 1.41 | | 3.0 | 2.03 | | 3.0 | 3.15 | |
| 9.0 | 2.15 | | 9.0 | 4.22 | | 9.0 | 6.09 | | 9.0 | 9.45 | |
| 15.0 | 3.58 | | 15.0 | 7.04 | | 15.0 | 10.15 | | 15.0 | 15.75 | |

Ocul, a round shaped LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.