


Olivio Down Lights















Product Code: IK-ROLIVIODL-8W-27K-WH-90C-24D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	648.38lm
Power	8W
Efficacy	140lm/w
CCT	2700K
CRI	>90
Beam Angle	24°
Light Distribution	Medium
LED Type	СОВ
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Round
Mounting Type	Recessed
Heads	Single Head
Heads Body Material	Single Head Aluminium Die cast
Body Material	Aluminium Die cast
Body Material Finish	Aluminium Die cast White
Body Material Finish Height	Aluminium Die cast White 4"
Body Material Finish Height Diameter	Aluminium Die cast White 4" 6-1/2"

Beam Spread (Options)									
Spot		15°	Medium	24°	Flood	38°	Wide Fl	.ood <mark>60°</mark>	
ft		Ø	ft	Ø	ft	Ø	ft	Ø	
3.0		0.72	3.0	1.41	3.0	2.03	3.0	3.15	
9.0		2.15	9.0	4.22	9.0	6.09	9.0	9.45	
15.0		3.58	15.0	7.04	15.0	10.15	15.0	15.75	

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link <u>⊀</u>

Installation Instructions Link 🕹

