


Thiea Down Lights

ITEM SKU#: 662187500584













Product Code: IK-RTHEIADL-8W-30K-WH-90C-38D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	683.5lm
Power	8W
Efficacy	140lm/w
CCT	3000K
CRI	>90
Beam Angle	38°
Light Distribution	Flood
LED Type	COB
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Sqaure
Mounting Type	Recessed
Heads	Single Head
Body Material	Aluminium Die cast
Finish	White
Length	2-7/8"
Height	4"
Cut Out	3"x3"
Optics	Darklight Technology Black, Silver
Width (W)	2-7/8"
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

Beam Spread (Options)										
Spot		15°	Mediun	n 24°	Flood	38°	Wide F	lood 60°		
ft		Ø	ft	Ø	ft	Ø	ft	Ø		
3.0		0.72	3.0	1.41	3.0	2.03	3.0	3.15		
9.0		2.15	9.0	4.22	9.0	6.09	9.0	9.45		
15.0		3.58	15.0	7.04	15.0	10.15	15.0	15.75		

Theia, a square LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid (global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

