


## Mica Pendant Lights

ITEM SKU#: 662187506678













## Product Code: IK-RMicaPL-30W-40K-WH-90C-15D

| Lumen Output 2700lm  Power 30W  CCT 4000K  CRI >90  Beam Angle 15°  Light Distribution Spot  LED Light Source Osram SOLERIQ S 19  Start Time Instant  Driver Stand Alone (included)  Operating Position No Swiveling Type  Dimming Triac Dimming / 0-10 V Dimming  Heads Single Head  Finish White  Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure | Voltage            | 100 - 277 V AC, 50-60 Hz   |
|---|--------------------|--|
| CCT 4000K  CRI >90  Beam Angle 15°  Light Distribution Spot  LED Light Source Osram SOLERIQ S 19  Start Time Instant  Driver Stand Alone (included)  Operating Position No Swiveling Type  Dimming Triac Dimming / 0-10 V Dimming  Heads Single Head  Finish White  Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure                                 | Lumen Output       | 2700lm   |
| CRI >90  Beam Angle 15°  Light Distribution Spot  LED Light Source Osram SOLERIQ S 19  Start Time Instant  Driver Stand Alone (included)  Operating Position No Swiveling Type  Dimming Triac Dimming / 0-10 V Dimming  Heads Single Head  Finish White  Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure  | Power              | 30W  |
| Beam Angle 15° Light Distribution Spot LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 5-1/8" Height 5-3/8" Optics Reflective Cup Structure  | ССТ                | 4000K  |
| Light Distribution Spot  LED Light Source Osram SOLERIQ S 19  Start Time Instant  Driver Stand Alone (included)  Operating Position No Swiveling Type  Dimming Triac Dimming / 0-10 V Dimming  Heads Single Head  Finish White  Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure   | CRI                | >90  |
| Start Time Instant  Driver Stand Alone (included)  Operating Position No Swiveling Type  Dimming Triac Dimming / 0-10 V Dimming  Heads Single Head  Finish White  Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure   | Beam Angle         | 15°  |
| Start Time Instant  Driver Stand Alone (included)  Operating Position No Swiveling Type  Dimming Triac Dimming / 0-10 V Dimming  Heads Single Head  Finish White  Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure   | Light Distribution | Spot   |
| Driver Stand Alone (included)  Operating Position No Swiveling Type  Dimming Triac Dimming / 0-10 V Dimming  Heads Single Head  Finish White  Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure   | LED Light Source   | Osram SOLERIQ S 19   |
| Operating Position No Swiveling Type  Dimming Triac Dimming / 0-10 V Dimming  Heads Single Head  Finish White  Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure  | Start Time         | Instant  |
| Dimming Triac Dimming / 0-10 V Dimming  Heads Single Head  Finish White  Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure  | Driver             | Stand Alone (included)   |
| Heads Single Head  Finish White  Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure  | Operating Position | No Swiveling Type  |
| Finish White  Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure   | Dimming            | Triac Dimming / 0-10 V Dimming                                   |
| Length 5-1/8"  Height 5-3/8"  Optics Reflective Cup Structure   | Heads              | Single Head  |
| Height 5-3/8"  Optics Reflective Cup Structure  | Finish             | White  |
| Optics Reflective Cup Structure   | Length             | 5-1/8"   |
|   | Height             | 5-3/8"   |
| - 1 (P)   | Optics             | Reflective Cup Structure   |
| Width (W) 5-1/8"  | Width (W)          | 5-1/8"   |
| Application Area Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance   | Application Area   | Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance |

| Bearn Spread (Options) |  |        |     |     |       |   |     |     |       |  |  |  |
|------------------------|--|--------|-----|-----|-------|---|-----|-----|-------|--|--|--|
| Spot 15°               |  | Medium |     | 30° | Flood |   |     | 45° |       |  |  |  |
| ft                     |  | Ø      | ft  |     | Ø     | f |     |     | Ø     |  |  |  |
| 3.0                    |  | 0.72   | 3.0 | ١ / | 1.41  | 3 | .0  |     | 2.03  |  |  |  |
| 9.0                    |  | 2.15   | 9.0 | /   | 4.22  | 9 | .0  |     | 6.09  |  |  |  |
| 15.0                   |  | 3.58   | 15. | 00  | 7.04  | 1 | 5.0 |     | 10.15 |  |  |  |

Mica is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

